

PUNTALE ROTONDO - ROUND PIN



Articolo Type	Sezione mm ² Section mm ² (AWG)	B	E	A	L	d	D	Utensile art. Tool	Conf. pezzi Packing pcs.
BM 00150	0,25 ÷ 1,5	1,8	12	10,4	22,4	1,95	4,20	536 1661 534 5341	1000
BM 00151	(22-16)	1,8	9	10,4	20	1,95	4,20		1000
BM 00250	1,5 ÷ 2,5	1,8	12	11	23	2,45	4,80	536 1661 534 5341	1000
BM 00251	(16-14)	1,8	9	11	20	2,45	4,80		1000
BM 00350	4 ÷ 6 (12-10)	2,6	14	14	28	3,50	6,60	536 1661 534 5341	500

IMQ - c.s. E-B170 (0,5-1,5 mm²) E-B171 (1,5-2,5 mm²) E-B172 (4-6 mm²)
 : file n° E 137735

PUNTALE PIATTO - BLADE PIN



Articolo Type	Sezione mm ² Section mm ² (AWG)	B	E	A	L	d	D	Utensile art. Tool	Conf. pezzi Packing pcs.
BM 00152	0,25 ÷ 1,5	2,8	9	9,5	18,5	1,9	4	536 1661 534 5341	1000
BM 00153	(22-16)	3	14,5	9,5	24	1,9	4		1000
BM 00252	1,5 ÷ 2,5	2,8	9	9,5	18,5	2,5	4,5	536 1661 534 5341	1000
BM 00253	(16-14)	2,8	16	9,5	25,5	2,5	4,5		1000
BM 00352	4 ÷ 6	2,8	10,4	14	24	3,5	6,6	536 1661 534 5341	500
BM 00353	(12-10)	4,5	18	14	32	3,5	6,6		500

La confezione pezzi si intende come multiplo di 10 scatolette.
 Packing are intending multiple of intern 10 boxes.

CONNETTORE RAPIDO - RAPID CONNECTOR



Materiale involucro isolante: (PP) polipropilene
 Tensione nominale: 300 V
 Temperatura d'esercizio: T 90°C



Housing material: (PP) polypropylen
 Voltage rating: 300 V
 Maximum temperature of exercise: T 90°C

Articolo Type	Sezione mm ² Section mm ² (AWG)	A	B	L	Conf. pezzi Packing pcs.
BM 00110	0,25 ÷ 1 (22-18)	15,3	10	20	500
BM 00210	1,25 ÷ 2,5 (18-14)	15,9	10	20	500
BM 00310	4 ÷ 6 (12-10)	17,5	13	21	500